

General Description

The ZM430N06S combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$.


Features

- Advance high cell density Trench technology
- Low $R_{DS(ON)}$ to minimize conductive loss
- Low Gate Charge for fast switching
- Low Thermal resistance

Application

- MB/VGA Vcore
- SMPS 2nd Synchronous Rectifier
- POL application


Product Summary



$$V_{DS} = 60V$$

$$R_{DS(ON)} = 43m\Omega$$

$$I_D = 5.5A$$



SOP-8

Ordering Information:

Part NO.	ZM430N06S
Marking	ZM430N06
Packing Information	REEL TAPE
Basic ordering unit (pcs)	4000

Absolute Maximum Ratings ($T_C = 25^\circ C$)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ^②	$I_{D@TC=25^\circ C}$	5.5	A
	$I_{D@TC=75^\circ C}$	4.2	A
	$I_{D@TC=100^\circ C}$	3.5	A
Pulsed Drain Current ^①	I_{DM}	15	A
Total Power Dissipation ^②	$P_D@TC=25^\circ C$	3.4	W
Total Power Dissipation	$P_D@TA=25^\circ C$	0.69	W
Operating Junction Temperature	T_J	-55 to 150	$^\circ C$
Storage Temperature	T_{STG}	-55 to 150	$^\circ C$

•Thermal resistance

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal resistance, junction - case ^②	R _{thJC}	-	-	36	° C/W
Thermal resistance, junction - ambient	R _{thJA}	-	-	180	° C/W
Soldering temperature, wavesoldering for 10s	T _{sold}	-	-	265	° C

•Electronic Characteristics

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	60			V
Gate Threshold Voltage	V _{GS(TH)}	V _{GS} =V _{DS} , I _D =250uA	1.2		2.5	V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =60V, V _{GS} =0V			1.0	uA
Gate- Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V			±100	nA
Static Drain-source On Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =5.5A		43	50	mΩ
		V _{GS} =4.5V, I _D =4.5A		75	85	mΩ
Forward Transconductance	g _{FS}	V _{DS} =10V, I _D =5A		10		s
Source-drain voltage	V _{SD}	I _S =5.5A			1.28	V

•Electronic Characteristics

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =25V f = 1MHz	-	800	-	pF
Output capacitance	C _{oss}		-	110	-	
Reverse transfer capacitance	C _{rss}		-	95	-	

Gate Charge characteristics(Ta= 25°C)

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Total gate charge	Q _g	V _{DD} =25V I _D = 5A V _{GS} = 10V	-	12	-	nC
Gate - Source charge	Q _{gs}		-	5	-	
Gate - Drain charge	Q _{gd}		-	4	-	

Note: ① Pulse Test : Pulse width ≤ 300μs, Duty cycle ≤ 2% ;

② Device mounted on FR-4 substrate PC board, 2oz copper, with thermal bias to bottom layer 1inch square copper plate;



Fig.1 Power Dissipation Derating Curve




Fig.2 Typical output Characteristics




Fig.3 Threshold Voltage V.S Junction Temperature




Fig.4 Resistance V.S Drain Current




Fig.5 On-Resistance VS Gate Source Voltage




Fig.6 On-Resistance V.S Junction Temperature




Fig.7 Gate Charge Measurement Circuit




Fig.8 Gate Charge Waveform




Fig.9 Switching Time Measurement Circuit




Fig.10 Switching Time Waveform




Fig.11 Avalanche Measurement Circuit





Fig.12 Avalanche Waveform



•Dimensions(SOP8)

Unit: mm

SYMBOL	min	TYP	max	SYMBOL	min		max
A	4.80		5.00	C	1.30		1.50
A1	0.37		0.47	C1	0.55		0.75
A2		1.27		C2	0.55		0.65
A3		0.41		C3	0.05		0.20
B	5.80		6.20	C4	0.19	0.20	0.23
B1	3.80		4.00	D		1.05	
B2		5.00		D1	0.40		0.62

